

List of Tables

Table 1.1	Common humidity variables and their properties. Information is based on Folland (1977), Elliott (1995), WMO (1996), McIlveen (1998) and van Wijngaarden & Vincent (2005).	22
Table 1.2	Key studies of surface humidity. QC stands for quality control.	23-25
Table 1.3	Trends for regionally averaged land surface air T and sea surface T . Units are $^{\circ}\text{C } 10\text{yr}^{-1}$. Significance at the 5 % level (according to statistical tests described in references for each dataset) is shown by bold type. LSAT stands for land surface air temperature and acronyms refer to dataset names.	26
Table 2.1	Equations for calculating e where T_{dw} is in $^{\circ}\text{C}$ and e and P are in hPa.	38
Table 3 <i>i</i>	Median differences (normalised units) between monthly mean e from hourly data and from other sampling frequencies for all case study stations.	47
Table 3.1	Case study station information log. Information is taken from ISH documentation provided by NCDC. H stands for hourly and H+ stands for hourly or more frequently.	75-76
Table 3.2	Results of the Bad Values QC for the case study stations. Results show the percentage of humidity data failing each test for all thirty three case study stations by latitude band where Polar covers from 60° to 90° , Extra-tropical covers from 20° to 60° and Tropical covers from 0° to 20° in each hemisphere.	77
Table 3.3	Greenland and Alaskan stations analysed for evidence of ‘cutoffs’ at low temperatures. Greenland stations begin with 04 and Alaskan stations begin with 70.	77
Table 3.4	Stations where less than 90 % of the data contain humidity values by 10°C bin and year. Continued from previous page. Percentages of T data with simultaneous T_{dw} reported are shown in parentheses. There must be at least 10 observations per bin for the test to be carried out. Station WMO IDs are substituted with letters where Ga is 702220, Th is 042020, Ki is 783970, Pa is 723710, Gl is 837460, Sv is 284400, Ks is 637080, Gi is 726650, Co is 711200, Dh is 404160 and Tu is 607150.	78-79

Table 3.5	Timezone QC test criteria and results. All tests check for similarity of the annual mean DC to the station mean DC using annual mean r value vectors described in the text. All five tests are described in section 3.2.1 <i>issue 6</i> . X denotes a fail. Grey shading separates station year groups.	80
Table 3.6	Approximate errors in measuring humidity due to differences in wind speed. Measurements are taken from two common wet-bulb thermometers, the Mercury-in-glass (MIG) and Resistance (R) thermometers, in comparison to assumed high accuracy measurement from a Dew-point hygrometer at three ventilation rates. Results are obtained from Folland (1977). Measurements are observed at 75 % RH where $T + T_w = 18$ °C such that $T_{dw} = 5.8$ °C, $e = 9.26$ hPa and $q = 5.70$ g kg ⁻¹ . Errors increase with decreasing RH.	80
Table 3.7	Station pairs for the Elevation QC.	81
Table 3.8	Results of homogenisation and second outlier check on the land data.	81
Table 3.9	Regionally averaged trends by season for q and RH. Values of largest magnitude for each region and each variable are in bold. Trends are created using the LSR method (Box 3.4). Significance at 5 % is shown with a * and at the 1 % with **.	81
Table 4.1	Documented issues with marine humidity measurements and error corrections.	125
Table 4.2	First stage quality control test descriptions.	125
Table 4.3	Summary of data removal from all quality control tests. Whole numbers indicate the number of observations. Percentages indicate that removed at that stage/iteration.	126
Table 4.4	Neighbour composite criteria for the Neighbour Check QC and the corresponding standard deviation range within which the candidate value must lie. Numbers in brackets denote order of preference for criteria.	126
Table 4.5	Regionally averaged trends in q and RH for each season. Values of largest magnitude for each region are in bold. Shaded boxes are where trends are strongest in the land data. Trends are created using the LSR technique (Box 3.4). Significance at 5 % is shown with a * and at the 1 % with **.	127
Table 4.6	Ship decks present around the period of the 1982 shift. Dark shading identifies decks where all pre-1982 data is recorded as integers. Lighter shading identifies decks where an integer bias is present in all data but stronger before 1982. Sourced from	127

the Hadley Centre Marine Data Bank, Brohan, P. *pers. comm.*.

Table 4.7	Regionally averaged trends for the entire record and post 1982 record. Trends for q are in $\text{g kg}^{-1} 10\text{yr}^{-1}$ and trends for RH are in $\% 10\text{yr}^{-1}$. Trends are significance tested using REML (Box 3.4) where ** denotes significance at the 1 % level and * denotes significance at the 5 % level.	128
Table 5.1	Statistical values for a comparison of the land and marine gridded datasets. The Global region covers 70 °S to 70 °N. The Northern Hemisphere region covers 20 °N to 70 °N. The Tropical region covers from 20 °S to 20 °N. The Southern Hemisphere covers from 70 °S to 20 °S. The r values are linear Pearson correlation coefficients. Shaded boxes highlight strongest r values and strongest trends for each region. Trends are calculated using the REML method (Box 3.4). Significance at 5 % is shown with a * and at the 1 % with **.	161
Table 5.2	Trends for surface q , RH and T . Shaded boxes (<i>italics</i>) highlight the region / season of maximum positive (negative) trend. Regions are as described in Table 5.1. Seasonal trends are created using the LSR technique (Box 3.4). All other trends are calculated using the REML method (Box 3.4). Significance at 5 % is shown with a * and at the 1 % with **.	161
Table 5.3	Categorising the twenty nine regions by trends in q and RH . Trends are calculated using the LSR method (Box 3.4). Region abbreviations and locations are shown in Figure 5.2. Starred regions are where both q and RH trends are significant at the 1 % or 5 % level. The accompanying timeseries and trends are shown as Figures 5.3a and b (split over two pages).	162
Table 6.1	Summary of potential marine data removal for Zero DPD and Repeats QC tests. Tests are implemented on each observing platform with a call sign (identification number) present.	182